


125 LB. CAST IRON FLANGED "Y" STRAINER

MODEL: I8-125



PRESSURE-TEMPERATURE RATINGS	
STEAM: 3/4" to 12"	125 psi @ 450° F
STEAM: 14" to 18"	100 psi @ 350° F
WOG: 3/4" to 12"	200 psi @ 150° F
WOG: 14" to 18"	150 psi @ 150° F

SERVICE RECOMMENDATIONS

The I8-125 is designed to provide economical & dependable protection to mechanical equipment. Self cleaning is easily accomplished by opening the plug or valve connected to the blowoff outlet (not supplied).

FEATURES

All sizes feature a bolted cover. The cover has a recessed seat which assures correct screen fit. There are bosses located at the inlet and outlet flanges for the installation of gauges (not supplied).

SCREENS

Heavy gauge 304 stainless steel screens are normally furnished in the following perforations:

SERVICE:	3/4" - 4"	5" to 18"
Steam:	.045"	.062"
Liquid :	.062"	1/8"

Other materials, such as Monel, Hastelloy C, & Alloy-20 are available. Other perforation sizes and/or mesh lining is also available.

CONSTRUCTION

The body and cover are constructed from Cast Iron (ASTM A126 B), and the flat gasket is non-asbestos. The blowoff outlets are tapped NPT, and are not normally supplied with plugs.

DIMENSIONS & WEIGHTS APPROXIMATE
(Apply for certified drawings)

INDIVIDUALLY HYDROSTATICALLY TESTED

Size in.	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"	5"	6"	8"	10"	12"	14"	16"	18"
mm	20	25	32	40	50	65	80	100	125	150	200	250	300	350	400	450
A	7 3/8	7 3/8	7 1/2	7 1/2	7 7/8	10	10 1/8	12 1/8	15 5/8	18 1/2	21 5/8	25 3/4	29 7/8	35	38 3/4	43 1/8
B	3 3/4	3 7/8	4 3/4	4 3/4	5 1/4	6 1/2	7	8 1/4	11 1/4	13 1/2	15 1/2	18 1/2	21 3/4	27	26 1/2	31
C (NPT)	1/2	1/2	1/2	1/2	1/2	1	1	1 1/2	2	2	2	2	2	2	2	2
WT (lb)	10	10	13	13	18	28	34	60	95	133	247	370	579	863	1380	2272

Also available in sizes 20" & 24"



Purple Engineering

Australian Distributor:

Phone: +61-1300 62 40 20
 Fax: +61-8-6323 0605
 Email: info@PRPL.com.au
 Skype: Purple.Engineering