

R. B
5" to 8"

NOTES:

- 01. Flanged Connections as per BS 10 Table E Flat Face.
- 02. Cover Clamp (Item 10) for 100 mm, 125 mm and 150 mm Size
- 03. No Foot Pad for Size 25 mm
- 04. 7/16"Ø Slotted Foot Pads For Size 50 mm
- 05. 1/2" Ø Slotted Foot Pads for Size 65 mm and 80 mm
- 06. 9/16" Ø Holed Foot Pads for Size 100 mm, 125 mm and 150 mm
- 07. 5/8" Ø Slotted Foot Pads for Size 200 mm
- 08. Dimensions 'B' and 'D' are from Bottom of Strainer
- 09. Dimension 'G' (NPT) (Item No 8) is measured as Outside Diameter of Threaded Part of Drain Plug
- 10. Item 9, Body Plug is not to be used as Drain.
- 11. 'B' and 'D' in 25 mm Size will be measured with Drain Plug Installed
- 12. Item No 3 has Viton O Ring Groove Fitted in Cover to achieve tight sealing.
- 13. Max Working Pressure: 200 PSI (14 Kg/cm²) at 100°F (38°C)
- 14. Viton Rubber Seal will be provided between Body and Filter Screen Contact Area.
- 15. 200 mm (8") Size Cover & Yoke will be as per above shown drawing.

Valve Dimension							Flange Dimensions						
Size	Α	В	С	D	G	Н	J	K	L	М	N	0	Р
25	194	280	102	143	21			109	115	83	8	4	14
50	268	372	172	197	21	140	64	146	150	114	12	4	18
65	295	417	202	227	16.5	165	73	168	165	127	12	4	18
80	334	476	203	270	16.5	178	80	185	185	146	13	4	18
100	425	500	272	273	21	254	99	238	215	178	14	8	18
125	460	650	272	392	21	254	118	257	255	210	15	8	18
150	499	735	272	465	21	254	127	275	280	235	18	8	22
200	686	950		693	48	400	219	394	335	292	19	8	22
												Т	OTAL

L = Flange OD, M = PCD, N = Thickness, O = No. of Holes, P = Hole Diameter All Dimensions are in mm (Dimensions Tolerance : + 3 mm)

	SIGN	DATE					
DRN.	SKP	04-04-19					
CHD.	KMP	04-04-19		POT STR	CUEET NO		
APPD.							SHEET NO.
SCALE	N.T.S.						
i C)=				MATERIAL:-	AS SHOWN	QTY:-
Purple Engineering			00 62 4020 RPL.com.au Engineering	Providing Equipment for: Oil & Gas Industry Pipeline Industry Marine Industry	DRG. NO.	ACE-BI-451-2018	REVISION