

Phone: (+61) 1300 62 4020 Email: info@PRPL.com.au Skype: Purple.Engineering

Providing Equipment for: Oil & Gas Industry Pipeline Industry Marine Industry Power Generation

ASTM CLASS 800 FORGED STEEL Y-STRAINER

Model: ACE-YF-800

Feature

SS-304 Perforated Screen + Mesh #40 lining (400 Micron)

Y Type Structure

Connection: Threaded End, Socket End

Thread Type: NPT, BSPT, DIN

Working Temperature: $\,$ -15 c $^{\sim}$ 440 c OR 5.4~822.6 $^{\circ}\mathrm{F}$ (A105)

-25 c ~ 524 c OR -14.4~957.6 °F (S.S.)

Material: A105, F304, F316, F11, F22, F304L, F316L

3.1 Certification

Standard

Manufacture and Design API 602. API 6D. API

Inspection and Test 594 API 598


Parts and Material

NO.	Part Name	Material						
1	BODY	A105	F304	F316				
2	SCREEN	STAINLESS STEEL						
3	GASKET	GRAPHITE+304 GRAPHITE+316						
4	CAP	A105	F304	F316				
5	BLOW OFF PLUG	Optional - Untapped						
6	CAP BOLT	A193 E	37	A193 B8				

^{*} Special alloys are available upon request







Dimensions (mm):

INCH	DN Stock	D Thread	D Socket	b	L	н	Weight KG
1/2"	15	15	21.8	9.6	98	84	2.7
3/4"	20	20	27.1	12.7	98	84	2.5
1"	25	25	33.8	12.7	120	102	6.3
1-1/4"	32	32	42.6	12.7	140	114	9.2
1-1/2"	40	40	48.7	12.7	140	114	9.2
2"	50	50	61.1	15.9	170	145	10.3

- * We reserve the rights of any alternative dimension without any notice. Please reconfirm exact dimensions at the time of order.
- ** Stock strainers to be machines by end user to Threaded or Socket weld or other connection types.



Australian Distributor

 Phone:
 1300 62 40 20

 Fax:
 +61-8-6323 0605

 Email:
 info@PRPL.com.au

 Skype:
 Purple.Engineering



Purple Engineering